

Installation Guide

Insulate your garage door with Foilboard® Rigid Panel Insulation

Garage Door Insulation

Required to install

1. Foilboard Spacer Blocks FB 071



2. Foilboard Silver Tape FB 062



3. Knife



- Australian made
- Lightweight
- Easy to install
- High thermal efficiency
- Rigid insulation
- Size of sheet 2400x1200
- Coverage 2.88m²

Installing FOILBOARD® Behind Garage Door:

1. Measure the width of each horizontal panel and cut the FOILBOARD® Green 15 to size using a straight edge and Snap Blade Knife. The FOILBOARD® should be cut across the width for ease of installation.
2. Using FOILBOARD Silver Insulation Tape seal all exposed edges of the FOILBOARD®.
3. Using FOILBOARD Spacer Blocks stick Spacer Blocks to one side of the FOILBOARD®.
4. Using a suitable High Temperature Resistant adhesive / silicone, adhere the FOILBOARD® to the inside of the Metal Tilt Panel. (Place high temp adhesive / silicone to the Spacer Blocks only)
5. Repeat the above 4 steps for all Panels.



You can also check out our installation videos online at - foilboard.com.au



Tape all joins with Foilboard® Silver Insulation tape.

Using FOILBOARD® Spacer Blocks with the FOILBOARD® will provide an Air Cavity that greatly increases the insulation performance.

FOILBOARD® comes in a range of thicknesses to suit any project. Visit the website for details.