



## Joinery Connection Strip - Exterior

CONTEGA® EXO is designed for use as a weathertight connection around exterior edge of windows and doors. It is a non-wicking, non-porous, flexible adhesive strip that is versatile for use in timber, masonry and concrete structures. The tape has slack for expansion to allow for relative motion between components over time, it provides a long-term durable seal. CONTEGA® EXO has adaptable installation options, provided by three strips of adhesive, and can also be plastered or rendered over on the fleece side. It is vapour-permeable ensuring your structure remains dry and durable.

- ✓ Effective weathertight seal around windows and doors
- ✓ Outstanding adhesion on cold and/or wet surfaces
- ✓ Flexible and expandable, to accommodate building movement
- ✓ Thin, highly pliable and easily formed around corners and shapes
- ✓ Airtight connection for the life of the building



20 03 2020



NEW ZEALAND  
0800 PRO CLIMA (776 254)  
Technical: [support@proclima.co.nz](mailto:support@proclima.co.nz)  
General: [welcome@proclima.co.nz](mailto:welcome@proclima.co.nz)  
[www.proclima.co.nz](http://www.proclima.co.nz)

AUSTRALIA  
1800 PRO CLIMA (776 254)  
[support@proclima.com.au](mailto:support@proclima.com.au)  
[welcome@proclima.com.au](mailto:welcome@proclima.com.au)  
[www.proclima.com.au](http://www.proclima.com.au)





### Technical Data

Carrier material:	double-layer PP fleece and TEEE functional film
Release material:	silicone-coated PE film
Temperature resistance:	long term -40 °C to +90 °C
Installation temperature:	above -10 °C
UV stability and outdoor exposure:	90 days
Colour:	black
Storage:	cool and dry

### IMPORTANT INFORMATION

- Thin, highly pliable and easily formed into corners and shapes
- Equipped with an expansion joint to accommodate building movement
- Outstanding adhesion in wet and cold conditions
- Fleece side can be plastered or rendered over

### PRODUCT DESCRIPTION

CONTEGA® EXO is a UV stabilised, vapour-permeable, external connection adhesive strip which makes effective connections to penetrations through wall assemblies such as windows and doors. It forms an essential part of your weather resistive barrier (WRB) system. Made from polypropylene with acrylate adhesive, it has excellent workability and adhesion for effective and durable air seals.

### WEATHER EXPOSURE

This product is designed to withstand up to 90 days of UV exposure during installation. Construction should be detailed to prevent direct continued sunlight onto the product in service.

### APPLICATION NOTES

Before application, substrate should be brushed or wiped clean to provide effective adhesion. Surfaces should be even and smooth enough to provide a clean connection. Surfaces must be free of grease, silicone and other water repellent substances. The product should be applied using the pro clima PRESSFIX tool to activate the pressure sensitive adhesive and ensure a long-term durable seal.

The bond must not be subjected to tensile strain over time. Any load borne by the product must be transferred to the substrate or other supporting materials as necessary.

### Delivery Form

ID CODE	LENGTH	WIDTH	QTY
15844	30 m	85 mm	1
1AR01266	30 m	120 mm	1



NEW ZEALAND  
0800 PRO CLIMA (776 254)  
Technical: [support@proclima.co.nz](mailto:support@proclima.co.nz)  
General: [welcome@proclima.co.nz](mailto:welcome@proclima.co.nz)  
[www.proclima.co.nz](http://www.proclima.co.nz)

AUSTRALIA  
1800 PRO CLIMA (776 254)  
[support@proclima.com.au](mailto:support@proclima.com.au)  
[welcome@proclima.com.au](mailto:welcome@proclima.com.au)  
[www.proclima.com.au](http://www.proclima.com.au)

